

K-355

DOUBLE-SIDED TISSUE TAPE

APPLICATIONS

A high performance double-coated tissue tape. Designed for splicing paper, fiberboard and films. Ideal for splicing corrugated paper. K-355 is excellent for a wide variety of laminating and bonding applications. Suitable for use with metal, glass, plastic materials (ABS, PET) and for nameplate bonding applications

FEATURES/BENEFITS

- The **high shear – high temperature adhesive** system offers consistent performance and insures a successful splice under a variety of operating conditions.
- Excellent **quick stick** and initial adhesion properties for easy application to the corrugated paper or material to be spliced or bonded.
- **User friendly** - The poly coated paper release liner removes easily and the tissue carrier allows for easy hand tearing.
- Solvent, chemical and UV resistant.

TECHNICAL DATA

Adhesive	: Modified Acrylic
Carrier	: Tissue
Tape thickness	: 4.0 mils
Interliner	: Poly Coated Paper
Adhesion to steel	: 50 oz/inch
Initial tack	: 20 - 32 (Ball No.)
Initial tack	: 1.50 – 2.10 (Loop Tack)
Temperature Range	: -10° F to +250° F (Long term)
	: 400° F (Short term)
Shelf Life	: 1 Year (DOM)
Recommended Storage	: 60°- 80° F @ 40 – 60% Relative Humidity

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.