

## **K-354**

### **DOUBLE-COATED FILM TAPE**

#### **APPLICATIONS**

A multi-purpose double-coated polyester film tape. Designed for splicing paper, fiberboard and plastic films. Ideal for high temperature splicing, holding and fastening applications.

#### **FEATURES/BENEFITS**

- The **high tack – high temperature adhesive** system offers consistent performance and insures successful splices and bonds under a variety of operating conditions.
- Excellent **quick stick** and initial adhesion properties for easy application to a variety of substrates and materials to be laminated, spliced or bonded.
- **User friendly** - The PE coated paper release liner removes easily and is ideal when good die cutting characteristics and dimensional stability are needed.
- Solvent, chemical and UV resistant.

#### **TECHNICAL DATA**

Adhesive	: Modified Solvent Based Acrylic
Carrier	: 0.50 mil Polyester Film
Tape thickness	: 3.5 mils
Liner	: 60# PE Coated Kraft Paper Liner
Tack	: 20 J. Dow No.
Peel Adhesion	: 42 oz/inch
Shear Strength	: > 24 hrs. @ 77° F (2.2 lb/1" x 1") PSTC-7
Temperature Range	: -4° F to 356° F

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.