

**K-370****HIGH BOND DOUBLE-COATED FILM TAPE****APPLICATIONS**

A high performance double-coated white UPVC film tape. Designed for demanding bonding applications. Ideal for attaching decorative trim, such as PVC profiles for the furniture industry. Excellent for the trophy mounting industry, attaching nameplates, signs and graphics in the appliance, telecommunications and construction industries.

**FEATURES/BENEFITS**

- Excellent resistance to solvents, chemicals, UV and heat.
- Permanent bonding to most substrates, such as metal, wood, glass, cement and plastic.
- Excellent plasticizer migration resistance.
- Exceptional bonding to low energy surfaces.

**TECHNICAL DATA**

Adhesive	: Modified Acrylic	
Carrier	: UPVC 50u	
Liner	: Glassine Paper	
Tape thickness	: 9.0 mils (0.23mm)	ASTM D-1000
Initial Tack (Ball No.)	: 10	JIS Z0237-12
Tensile Strength	: 14.3 lbs/inch (6.5 kg/25mm)	ASTM D-1000
Peel Adhesion (After 15 min.)		
Stainless Steel	: 125 oz/inch	
ABS	: 118 oz/inch	
PVC	: 108 oz/inch	ASTM D-1000
PET	: 90 oz/inch	
PE	: 50 oz/inch	
PP	: 43 oz/inch	
Temperature Resistance	: 170° F/80° C	PSTC-708

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.