

K-2208

DOUBLE-SIDED FOAM TAPE

APPLICATIONS

Designed to provide a superior bond between a wide variety of substrates. Ideal for attaching automotive trim and nameplates, for attaching signs, mirrors and graphics in the appliance, telecommunications and construction industries.

FEATURES/BENEFITS

- Quick stick for efficient operation
- Good shear strength adhesive system offers secure, long term bonding performance.
- Flexible foam material provides comfortable mating to contour surfaces.
- 1/32" foam carrier offers gap filling performance when bonding uneven surfaces.

TECHNICAL DATA

Adhesive	: Solvent Based Rubber
Carrier	: 1/32" Polyethylene Foam
Liner	: 60 lb White Glassine Paper
Tape thickness	: 0.0313 inches (.80mm)
Tack	: 7 J. Dow No.
Peel Adhesion	: 123 oz/inch (over 3.5 kg/25mm) PSTC-3
Shear Strength	: Over 100 hrs with 70.6 oz loading on 1" x 1" (2.0 kg/ 25mm x 25mm) sandwich holding of 2 stainless steel plates at 77°F (25°C)
Heat Resistance	: -14°F - 122°F (-10°C - 50° C)

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.