

K-4230

DOUBLE-SIDED FOAM TAPE

APPLICATIONS

Designed to provide a superior bond between a wide variety of substrates. Ideal for attaching automotive trim and nameplates, for attaching signs, mirrors and graphics in the appliance, telecommunications and construction industries.

FEATURES/BENEFITS

- Good resistance to solvents, chemicals, UV and heat.
- High shear adhesive system offers secure, long term bonding performance.
- Excellent weathering properties – ideal for outdoor mounting applications.
- 1/8" foam carrier offers gap filling performance when bonding uneven surfaces.
- Isolates and dampens vibration and shock – flexible, moldable, compressible.

TECHNICAL DATA

Adhesive	: Solvent Based Acrylic	
Carrier	: 1/8" Polyethylene Foam	
Liner	: 60 lb White Glassine Paper	
Tape thickness	: 0.125 inches (3.175mm)	
Tack	: 20 J. Dow No.	
Peel Adhesion	: 105.8 oz/inch (3.0 kg/25mm)	PSTC-3
Shear Strength	: Over 24 hrs with 35.3 oz loading on 1" x 1" (1.0kg/ 25mm x 25mm) sandwiched between 2 stainless steel plates	
Tensile Strength	: 528 oz / inch (15 kg / 25mm x 25mm)	
Heat Resistance	: -4°F - 176°F (-20°C - 80° C)	

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.