

K-4960

HIGH BOND DOUBLE-COATED FILM TAPE

APPLICATIONS

A high performance double-coated polyester film tape. Designed to provide a secure bond under high temperature conditions. Ideal for attaching automotive trim and nameplates, for attaching signs and graphics in the appliance, telecommunications and construction industries.

FEATURES/BENEFITS

- Excellent resistance to solvents, chemicals, UV and heat.
- Ideal for mounting on ABS plastic plates in the automotive industry.
- Excellent plasticizer migration resistance.
- Exceptional bonding to low energy surfaces.

TECHNICAL DATA

Adhesive	: Acrylic PSA on both sides	
Carrier	: 1 mil PET	
Liner	: Red Polyolefin Film – 2.5 mil	
Tape thickness	: 8 mils (0.01mm)	
Tack	: 16 J. Dow	
Adhesion to Steel	: 90 oz/inch (2555 g/25mm)	PSTC-3
Adhesion to PP	: 70 oz/inch (2275 g/25mm)	
Adhesion to PE	: 35 oz/inch (2400 g/25mm)	
Service Temperature	: 390° F to -4° F (180° C to -20° C)	

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.