

PC 628

Industrial Grade
Vinyl-coated Gaffers Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Gaffer's tape in A/V, TV, photography, theatrical and motion picture industries to hold wiring, lighting, stage props and to color code
- > Masking silk screen frames
- > Protection

ADVANTAGES AND BENEFITS

- > Waterproof backing
- > Excellent holding power
- > Conformable
- > Durable
- > Excellent weathering features
- > Very high tensile strength



CONSTRUCTION

Overall Grade/Function: Industrial Grade
 Backing: Lusterless, vinyl film with a cotton cloth carrier
 Adhesive: Natural rubber

COLOR(S)



STANDARD WIDTH(S)

48 mm 72 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	46 lbs/in width	80.6 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.47 N/10 mm
Thickness	12.0 mils	0.30 mm
Elongation	5 %	5 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

"Shurtape" is a registered trademark of Shurtape Technologies, LLC

Form# TDS-PC628-06/12/2008