



K-121

HIGH-TEMPERATURE PAPER MASKING TAPE

APPLICATIONS

Designed for very high temperature paint masking and holding applications. Ideal for use where temperatures reach 350°F (177°C) for up to 30 minutes and clean removal is required. Suitable for use on treated metals, such as aluminum anodized surfaces. Clean removal can vary depending on the type of surface, processing conditions and types of paints or coatings. It is recommended to test the product under your application conditions.

FEATURES/BENEFITS

- K-121 utilizes a fine structured crepe paper for smooth application and flat edges for sharp, well defined paint lines.
- The high performance solvent rubber adhesive system features high initial tack properties and clean removal after exposure to oven temperatures up to 350°F (177°C) for 30 minutes.
- The specially treated paper backing exhibits high strength and excellent conformability.
- A special release coating provides a controlled unwind release for easy use and less waste.
- Available in custom widths and lengths and in die-cut form for spot masking applications.

TECHNICAL DATA

Adhesive	: Solvent Based Rubber
Backing	: Fine Structure Crepe Paper
Color	: Tan
Tape thickness	: 6.7 mils
Elongation	: 10%
Tensile strength	: 24 lbs/in/12kg/25mm
Adhesion to steel	: 36 oz/inch/3.83N/25mm
Standard length	: 60 yards

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.



K-166

GENERAL PURPOSE PAINT MASKING TAPE

APPLICATIONS

Designed for industrial and automotive paint masking applications that do not require a bake cycle. Ideal for commercial and residential painting applications. Also suitable for industrial holding and packaging applications. Temperature ranges from 50° F to 200°F (10°C to 93°C).

FEATURES/BENEFITS

- K-166 is conformable, with good edge tear resistance for masking irregularly shaped surfaces.
- The rubber based adhesive system features excellent quick stick properties.
- Easy to unwind off the roll.
- Ideal for the paint and sundries market.
- Available in custom widths and lengths and in die-cut form for spot masking applications.

TECHNICAL DATA

Adhesive	: Rubber Based
Backing	: Crepe Paper
Color	: Natural
Tape thickness	: 5.8 mils/0.14mm
Elongation	: 9%
Tensile strength	: 23 lbs/in/40.2 N/10mm
Adhesion to steel	: 39 oz/inch/4.26 N/10mm
Standard length	: 60 yards/55 meters

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.