



K-1402

DOUBLE COATED PERMANENT/REMOVABLE FILM TAPE

APPLICATIONS

A double coated film tape coated with a differential acrylic based adhesive system that features a permanent adhesive on the open side and a removable adhesive on the liner side. Designed for applications for mounting posters and signage temporarily on notice boards, window displays or other smooth surfaces. Removable adhesive side allows for easy removal without leaving adhesive residue.

FEATURES/BENEFITS

- Permanent adhesive side has very good adhesion properties to metal, paper and plastic materials. Excellent bonding to LSE (Low Surface Energy) substrates including PE and PP.
- Removable adhesive side provides a clean removal from a light duty bond on a variety of surfaces. The adhesive allows for re-usability when the bonded surface is kept clean.
- Very good UV and temperature resistance.

TECHNICAL DATA

Adhesive (Open Side)	: 1.50 mil Emulsion Acrylic – Open Side	
Adhesive (Liner Side)	: 1 mil Emulsion Acrylic – Liner Side	
Carrier	: 0.50 mil Transparent PET Film	
Release Liner	: 55 lb. White PE-Coated Paper	
Tape Thickness	: 3 mils without liner	
Initial Tack (Open Side)	: 32 oz per inch of width	PSTC-5
Initial Tack (Liner Side)	: 14 oz per inch of width	PSTC-5
Peel Adhesion (Open Side)	: 80 oz per inch of width	PSTC-101
Peel Adhesion (Liner Side)	: 30 oz per inch of width	PSTC-101
Shear Strength (Open Side)	: 24 hours	PSTC-107
Shear Strength (Liner Side)	: 168+ hours	PSTC-107
Service Temperature	: -40°F to 180°F (-20°C to 100°C)	

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the end user under actual conditions with intended substrates to determine if the product is suitable for the application.