



K-1404

DOUBLE COATED REMOVABLE FILM TAPE

APPLICATIONS

A double coated film tape coated with an acrylic based removable adhesive on both sides of a 1 mil polyester film carrier. Designed for applications that require a clean removal from both sides of the tape. Ideal for mounting posters and signage temporarily on notice boards, window displays or other smooth surfaces. Allows for removal without leaving adhesive residue on both sides of the tape.

FEATURES/BENEFITS

- Excellent tack and adhesion properties on both sides of a durable polyester film carrier.
- Removable adhesive on both sides provides for a clean removal after bonding on a variety of surfaces. The adhesive allows for re-usability when the bonded surface is kept clean.
- Very good UV and temperature resistance.

TECHNICAL DATA

Adhesive	: Emulsion Acrylic	
Carrier	: 1 mil Transparent PET Film	
Release Liner	: 55 lb White PE Coated Paper	
Tape Thickness	: 6 mils without liner	
Initial Tack (Both Sides)	: 14 oz/inch of width	PSTC-5
Peel Adhesion (Both Sides)	: 30 oz/inch of width	PSTC-101
Shear Strength (Both Sides)	: 168+ hours	PSTC-107
Service Temperature	: -40°F to 180°F (-20°C to 100°C)	

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the end user under actual conditions with intended substrates to determine if the product is suitable for the application.