

K-238**DOUBLE COATED PERMANENT/REMOVABLE FILM TAPE****APPLICATIONS**

A double coated film tape coated with a differential acrylic based adhesive system that features a permanent adhesive on the open side and a removable adhesive on the liner side. Designed for applications for mounting posters and signage temporarily on notice boards, window displays or other smooth surfaces. Allows for removal without leaving adhesive residue.

FEATURES/BENEFITS

- Permanent adhesive side has very good adhesion properties to metal, paper and plastic materials.
- Excellent bonding to High Surface Energy (HSE) plastics.
- Removable adhesive side adheres to a variety of substrates including glass, ABS and PVC without leaving adhesive residue upon removal.
- Very good UV and temperature resistance.

TECHNICAL DATA

Adhesive (Permanent Side)	: Modified Solvent Acrylic – Open Side	
Adhesive (Removable Side)	: Modified Solvent Acrylic – Liner Side	
Carrier	: 0.50 mils Transparent PET Film	
Release Liner	: 57 lb White PE-Coated Paper	
Tape Thickness	: 3.25 mils without liner	
Initial Tack (Permanent Side)	: 7.10 inches	ASTM 3121-94
Initial Tack (Removable Side)	: 9.80 inches	ASTM 3121-94
Peel Adhesion (Permanent Side)	: 55 oz per inch	ASTM D3330M-04
Peel Adhesion (Removable Side)	: 18 oz per inch	ASTM D3330M-04
Service Temperature	: -40°F to 140°F (212°F Short Term)	

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the end user under actual conditions with intended substrates to determine if the product is suitable for the application.