



K-370

HIGH BOND DOUBLE COATED FILM TAPE

APPLICATIONS

A high performance double coated white UPVC film tape. Designed for demanding bonding applications. For attaching decorative trim, such as PVC profiles for the window, automotive aftermarket and furniture industries. Excellent for the trophy mounting industry, attaching nameplates, signs and graphics in the appliance, electronics and construction industries. Ideal as a **Banner Hem Tape** for seaming vinyl banners.

FEATURES/BENEFITS

- Excellent resistance to solvents, chemicals, UV and heat.
- Permanent bonding to a wide variety of surfaces, such as metal, wood, glass, cement and plastic.
- Excellent plasticizer migration resistance.
- Exceptional bonding to High Surface Energy (HSE) substrates.
- Dimensionally stable construction allows for easy custom die cut parts.

TECHNICAL DATA

Adhesive	: Modified Solvent Acrylic	
Carrier	: White UPVC Film – 2 mils	
Release Liner	: 60 lb Mustard Glassine Paper – 3 mils	
Tape Thickness	: 8.50 mils without liner (0.21mm)	
Initial Tack	: J Dow No. 14	
Tensile Strength	: 15.40 lbs per inch of width (7.0 kg/mm ²)	ASTM D-1000
Peel Adhesion		
Stainless Steel	: 125 oz per inch of width	
ABS	: 118 oz per inch of width	
PVC	: 108 oz per inch of width	
PET	: 90 oz per inch of width	
PE	: 50 oz per inch of width	
PP	: 43 oz per inch of width	
Temperature Range	: -40°F to 194°F (-40°C to 90°C)	

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the end user under actual conditions with intended substrates to determine if the product is suitable for the application.