

K-4815B Double-Coated Polyethylene Foam Tape

PRODUCT DESCRIPTION

K-4815B is a high-performance double-coated polyethylene foam tape designed for bonding, mounting, and sealing applications requiring strong initial tack and long-term durability. Engineered with a solvent-based acrylic adhesive and reinforced with a closed-cell foam structure, this tape delivers excellent adhesion, vibration dampening, and gap-filling capabilities. Its flexible foam carrier provides resistance to water, chemicals, UV exposure, and temperature changes, making it ideal for indoor and outdoor applications.

KEY FEATURES

- Very high initial tack and peel adhesion
- Closed-cell polyethylene foam for sealing and cushioning
- Excellent resistance to water, chemicals, and UV
- Absorbs vibration and impact
- Ideal for uneven or irregular surfaces

APPLICATIONS

- Mounting emblems and nameplates
- Plastic trim and strip attachment
- Mirror and hook mounting
- Gap sealing and cushioning

TECHNICAL SPECIFICATIONS

Property	Value
Adhesive System	Solvent Acrylic
Carrier	Polyethylene Foam
Foam Density	4 PCF
Thickness	1/16" (1.5 mm)
Liner	PE Film
Liner Thickness	4 mil
Tape Color	Black
Service Temperature	-22°F to 176°F

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.