

## **K-297**

### **DOUBLE-COATED FILM TAPE**

#### **APPLICATIONS**

A high performance double-coated polyester film tape. Designed for splicing paper, fiberboard and plastic films. Ideal for high temperature splicing, holding and fastening applications. Excellent seaming tape for sailing cloths.

#### **FEATURES/BENEFITS**

- The **solvent based acrylic adhesive** system offers excellent solvent, chemical and UV resistance.
- Ideal for **bonding low surface energy substrates** as well as porous materials and textiles.
- **User friendly** – The heavy duty 80# paper release liner removes easily and is ideal when good die cutting characteristics and dimensional stability are needed.
- Excellent **low temperature** properties.

#### **TECHNICAL DATA**

Adhesive	: Modified Solvent Based Acrylic
Carrier	: 0.50 mil Polyester Film
Tape thickness	: 4.0 mils
Liner	: 80# PE Coated Kraft Paper
Tack	: 16 J. Dow No.
Peel Adhesion	: 56oz/inch
Shear Strength	: >24 hrs @ 77°F (2.2lb/1" x 1") PSTC-7
Temperature range	: -40°F to 212°F

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.