



K-4800 SERIES DOUBLE COATED FOAM TAPES

APPLICATIONS

Designed to provide a superior bond and seal for **window glazing** applications. Ideal for attaching automotive trim and nameplates, for attaching signs, mirrors and graphics in the appliance, telecommunications and construction industries. A versatile and economical double coated foam tape.

FEATURES/BENEFITS

- Good resistance to solvents, chemicals, UV light and heat.
- High shear strength adhesive system offers secure, long term bonding performance.
- Soft flexible foam carrier offers gap filling performance when bonding uneven surfaces.
- Isolates and dampens vibration and shock – flexible, moldable, compressible.
- AAMA certified for window glazing applications.

TECHNICAL DATA

Adhesive	: Solvent Based Acrylic
Carrier	: Closed Cell Polyethylene Foam
Colors	: White & Black
Liner	: Blue PE Film – 4 mils
Temperature Range	: -22°F to 176°F (-30°C to 80°C)

Product Number	: K-4808	K-4815	K-4824	K-4830
Tape Thicknesses	: 1/32" (0.8mm)	1/16" (1.5mm)	3/32" (2.4mm)	1/8" (3.0mm)
Foam Density	: 4 lbs./ft ³	4 lbs./ft ³	2.5 lbs./ft ³	2.5 lbs./ft ³
Loop Tack	: 134 oz/in	176 oz/in	127 oz/in	105 oz/in
Peel Adhesion	: 70 oz/in	124 oz/in	53 oz/in	53 oz/in
Standard Lengths	: 216 ft	150 ft	150 ft	75 ft

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.