



K-7060

ULTRA HIGH BOND DOUBLE COATED ACRYLIC FOAM TAPE

APPLICATIONS

Designed to replace mechanical fasteners like rivets and welds with a superior bond and seal on a wide variety of surfaces. Ideal for fastening trim and nameplates, for mounting signs, mirrors and attaching graphics in the P-O-P display, automotive, aerospace, appliance, telecommunications and construction industries.

FEATURES/BENEFITS

- Excellent resistance to solvents, moisture, heat and UV light.
- High shear strength adhesive system offers secure, long term bonding performance.
- Soft flexible foam carrier offers gap filling performance when bonding uneven surfaces.

TECHNICAL DATA

Adhesive	: Solvent Acrylic	
Carrier	: Closed Cell Acrylic Foam	
Colors	: White (W)	
Release Liner	: Red PE Film – 5 mils (0.13mm)	
Tape Thickness	: 25 mils without liner (0.6mm)	
Tensile Strength	: 100 lbs per inch ²	ASTM D--897
Adhesion to Steel		PSTC-101, ASTM D-3330
@ 20 minutes	: 11.2 lbs per inch of width	
@ 24 hours	: 12.3 lbs per inch of width	
@ 250 hours	: 11.8 lbs per inch of width	
Dynamic Shear		ASTM D-1002
@ 20 minutes	: 101 lbs per inch of width	
@ 24 hours	: 105 lbs per inch of width	
@ 250 hours	: 115.2 lbs per inch of width	
Service Temperature	: -4°F to 248°F (-20°C to 120°C)	
Standard Length	: 36yards (33 meters)	

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the end user under actual conditions with intended substrates to determine if the product is suitable for the application.