



## K-112

### AUTOBODY PAINT MASKING TAPE

#### APPLICATIONS

A premium yellow crepe paper coated with a natural rubber based adhesive system. Designed for critical paint masking applications in the automotive repair market. Waterproof and conformable with easy removal with no adhesive residue and with a temperature range of up to 248°F. Ideal for tabbing and bundling applications in printed circuit board layout applications and general industrial markets.

#### FEATURES/BENEFITS

- Conformable and waterproof paper provides clean, sharp paint lines and paint flaking resistance.
- Medium initial tack with controlled roll unwind for easy application.
- Good temperature stability with clean removal from a variety of surfaces.
- Engineered for use with traditional solvent based and water based paints.
- Available on a paper release liner for custom die cut shapes or sheets for spot masking.

#### TECHNICAL DATA

Adhesive	:	Natural Rubber
Backing	:	Paper
Color	:	Yellow
Tape Thickness	:	5.6 mils
Tensile Strength	:	25 lbs/in width
Adhesion to Steel	:	16 oz/in width
Elongation	:	8%
Temperature Range	:	0°F to 248°F (30 minutes)

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.