



K-114

HIGH PERFORMANCE PAINT MASKING TAPE

APPLICATIONS

A premium green crepe paper coated with a natural rubber based adhesive system. Designed for critical paint masking applications in the automotive repair market. Waterproof and conformable for wet sanding and paint masking applications with easy removal with no adhesive residue. Good temperature resistance. Ideal for tabbing and bundling applications in printed circuit board layout applications and general industrial applications where a high strength paper tape is required.

FEATURES/BENEFITS

- Conformable and waterproof paper provides clean, sharp paint lines and paint flaking resistance.
- High initial tack with controlled roll unwind for easy application.
- Good temperature stability with clean removal from a variety of surfaces including glass, plastics and rubber trims.
- Engineered for use with traditional solvent based and water based paints with no edge bleed.
- Available on a paper release liner for custom die cut shapes or sheets for spot masking.

TECHNICAL DATA

Adhesive	: Natural Rubber
Backing	: Paper
Color	: Green
Tape Thickness	: 7.5 mils
Tensile Strength	: 25 lbs/in width
Adhesion to Steel	: 26 oz/in width
Elongation	: 13%
Temperature Range	: 0°F to 212°F (60 minutes)
	: 0°F to 250°F (30 minutes)

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.