



tesa[®] 4101 PV2



Product Information

Adhesive film of hydrate cellulose for packaging

Product Description

tesa[®] 4101 PV 2 is based on a hydrate cellulose film coated with a rubber adhesive. The backing, which is composed of a sustainable material, is characterized by a high rigidity and low electrostatic charging. For this reason long strips of the tape can be dispensed without any curling effect is possible. The tape can easily be torn by hand.

Hydrate cellulose film can be cleanly cut (separated) by an subjacent tesa[®] tear strip.

Application Fields

tesa[®] 4101 PV 2 is mainly used for general packaging purposes, such as sealing of small boxes. The tape can be easily applied with tesa[®] desk dispensers.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------|-------------------|--------|
| • Backing material | hydrate cellulose | • Total thickness | 51 µm |
| • Type of adhesive | synthetic rubber | | 2 mils |

Properties/Performance Values

- | | | | |
|-----------------------|------|--------------------|----------------------|
| • Elongation at break | 25 % | • Tensile strength | 42 N/cm
24 lbs/in |
|-----------------------|------|--------------------|----------------------|

Adhesion to Values

- | | |
|---------|----------------------|
| • Steel | 6 N/cm
54.8 oz/in |
|---------|----------------------|



tesa[®] 4101 PV2

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04101>