



K-7501

ATG ACRYLIC TRANSFER TAPE

APPLICATIONS

An economical 1.7 mil glass fiber stabilized acrylic adhesive transfer tape. Designed for use in all types of ATG Applicators and in general purpose mounting and bonding applications. Ideal for core starting and splicing films, papers and foils. Also suitable use in the picture framing, bindery and trophy industry.

FEATURES/BENEFITS

- The **glass fiber stabilized** acrylic adhesive system offers easy slitting of custom widths with stable roll edges that resist adhesive oozing.
- Excellent **quick stick** and initial adhesion properties for easy application to a wide variety of materials for splicing, mounting or bonding applications.
- Available in 60 yard rolls on a 1" ID plastic core and fits all ATG dispensers.
- Excellent solvent, UV and aging resistance.

TECHNICAL DATA

Adhesive	: Acrylic (Fiber Reinforced)
Tape Thickness	: 1.7 mils (0.040mm)
Release Liner	: Gold Densified Paper
Liner Thickness	: 3.5 mils (0.09mm)
Core Size	: 1" ID Plastic
Peel Adhesion	: 25 oz/inch of width
Temperature Range	: -22°F to 302°F
Standard Widths	: ¼" (6mm), ½" (12mm), ¾" (19mm)
Standard Length	: 60 yards (55m)

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.