



K-7702

2 MIL ADHESIVE TRANSFER TAPE

APPLICATIONS

A premium 2 mil glass fiber stabilized acrylic adhesive transfer tape. Designed for general purpose mounting and bonding applications. **Acid free** acrylic adhesive system. Ideal for core starting and splicing films, papers and foils. Also suitable use in the picture framing, bindery, nameplate and trophy industry.

FEATURES/BENEFITS

- The **glass fiber stabilized** acrylic adhesive system offers easy slitting of custom widths with stable roll edges that resist adhesive oozing.
- Excellent **quick stick** and initial adhesion properties for easy application to a wide variety of materials for mounting or bonding applications.
- Ideal for making flying splices at elevated temperatures.
- Siliconized moisture stable liner allows for easy removal after application.
- Available in rolls up to 180 yards in length on a 3" ID paper core.
- Excellent solvent, UV and aging resistance.

TECHNICAL DATA

Adhesive	: Solvent Based Acrylic (Fiber Reinforced)
Tape Thickness	: 2.0 mils
Release Liner	: 55 lb Tan Kraft Paper
Liner Thickness	: 3.5 mils
Peel Adhesion	: 45 oz./inch of width
Temperature Range	: -22°F to 230°F
Standard Length	: 60 yards/55 meters (180 ft)

Note: The above are typical values obtained from tests recommended by the PSTC, ASTM, or government agencies and should not be used in writing specifications. The product should be thoroughly evaluated by the user under actual conditions with intended substrates to determine if the product is suitable for the application.